

JUL 02 2008

**Applicant: Proctor Jr. et al.
Application No.: 10/717,995****Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. - 29. Canceled.

30. (Newly added) A method in a base station for aligning a field unit comprising:

receiving a reverse link signal from a field unit;
determining a gross timing offset with respect to reverse link channels from other field units sharing the same reverse link logical channel;
calculating a metric associated with the received reverse link signal; and
selectively determining based on said metric whether said base station should control the alignment of said field unit.

31. (Newly added) The method of claim 30 further comprising:
transmitting a message to other base stations whether said base station is going to control the alignment of said field unit.

32. (Newly added) The method of claim 31 further comprising:
reporting said timing offset in the form of a timing command.

33. (Newly added) The method of claim 31 further comprising:
causing said reverse link signal to be orthogonally aligned with the signals from said at least one other field unit on the reverse link logical channel.

Applicant: Proctor Jr. et al.
Application No.: 10/717,995

34. (Newly added) The method of claim 33 further comprising:
determining a power level of the reverse link signal; and
providing feedback of the power level to the field unit in the form of a power
command or a power message.

35. (Newly added) The method of claim 30, wherein said base station does
not control the alignment of said field unit.

36. (Newly added) The method of claim 35 further comprising:
transmitting a message to other base stations that said base station is not
going to control the alignment of said field unit.

37. (Newly added) The method of claim 36, wherein said determination of
said base station not to control said alignment is based on at least one of the
following criteria: (a) a metric of the transmission path between the field unit and
at least one of the other base stations exceeds a threshold for a predetermined
timespan, (b) a metric of the transmission path between the field unit and at least
one of the other base stations exceeds a threshold relative to a metric of a
transmission path between said base station and the field unit for a predetermined
timespan, (c) a metric of the transmission path between said base station and the
field unit drops below an absolute metric, and (d) a metric of the transmission path
between at least one of the other base stations and the field unit exceeds an
absolute metric.

38. (Newly added) The method of claim 37, wherein the metric includes at
least one of the following: (a) power, (b) signal-to-noise ratio (SNR), (c) variance of
the power, (d) variance of the SNR, (e) between the orthogonally aligned path an
non-orthogonally aligned paths between the given field unit and said base station

Applicant: Proctor Jr. et al.
Application No.: 10/717,995

and said other base stations, relative ratio of the (i) power, (ii) SNR, (iii) variance of the power, or (iv) variance of the SNR, (f) bit error rate, and (g) energy per chip divided by the interference density (E_c/I_o).